


## IMPORTANT NOTE FOR SIG P226 PISTOLS


For optimum performance of an older SIG P226 with your Hogue Grips it is recommended that the trigger return spring be replaced with the "new" style spring which is available from SIG.

SIG redesigned the 226 frame in the mid 1990s and the new pistols come with a redesigned trigger return spring.

Your new Hogue Grip is designed to work with both the old and new frame and spring styles, however, the new spring works better under certain conditions with your Hogue Grip installed. For this reason it is recommended that you use the new style spring for duty use or any other use in which maximum reliability is necessary.



**NEW STYLE SPRING**



**OLD STYLE SPRING**

**SIGARMS, Inc.**  
18 Industrial Drive  
Exeter, NH 03833  
603-772-2302  
Fax: 603-772-9082  
www.sigarms.com

Hogue's Rubber Automatic Grip features add up to improved scores, comfortable shooting and dependable service.

- COBBLESTONE™ system is an efficient, non-slip, non-irritating stippling pattern that replaces conventional checkering.
- Hogue's Automatic Pistol Grips feel soft and resilient in your hand, yet are molded with reinforcing inserts which engage directly with the gun frame and grip screws for a rock-solid grip to frame fit.



Post Office Box 1138  
Paso Robles, California 93447  
805-239-1440 • Fax 805-239-2553  
www.getgrip.com

*The Originator and Maker of Monogrip®*  
**IMPORTANT CONSUMER AND  
WARRANTY INFORMATION  
ON BACK OF PACKAGE**

PPF - R-4 (REV. 2/03)

## A FEW WORDS ABOUT FIT

It is a fact that gun frame dimensions vary from gun to gun. No grip is shipped out unless it fits our guns properly. Please keep this in mind.

Because of frame variations, an occasional misfit may be encountered. Don't be alarmed! If your grip does not fit your gun's frame to your satisfaction, we will do whatever it takes to fit your grip, or exchange it for one that will.

Most of the time a simple phone call will remedy the situation. Before you call, make sure you have read the instructions and installed the grip properly.

It is imperative to make sure that every gun functions properly with aftermarket grips installed. This is especially important on any firearm that the grip comes in close proximity to working components such as the main-spring trigger bar, etc. Although the grip functions properly on our guns, it is the user's responsibility to assure that the grip functions properly on the gun fitted with a new grip. If you do not feel competent to check the proper function yourself, we suggest visiting your gunsmith to check this for you. **It is important to test fire a pistol fitted with new grips before using the field.**

If you have any problems installing your Hogue Grip please call us at (805) 239-1440. We will be glad to help make sure your grip fits perfectly.

## SAFETY


**Before working on your firearm, remove the magazine and make sure the GUN IS UNLOADED.**

## IMPORTANT!

Check all functions of your gun after grips are installed. **Test fire your gun.** This is especially important if weapon is to be used for law enforcement duty.

## SPECIAL INSTRUCTIONS FOR SIG SAUER PISTOLS

Due to a close tolerance fit in the decocker area and the nature of a wrap-around grip, you must install the decocker side (left side) first. It is necessary to "maneuver" the left panel carefully into the decocker area while slightly depressing the lever. The right panel will install in a simpler manner and must be done last.



**SIG P220**

For SIG Sauer P220 models, carefully remove the lockwashers from the original grips and use them along with the original screws in your new Hogue grip.

NOTE: for proper clearance on Serial Numbers below 219166, place the small plastic shim supplied inside the right grip panel as shown. For Serial Numbers 219166 and above, make sure the shim is removed.

**SEE REVERSE FOR  
P226 INSTRUCTIONS**